



HD-IR3VB

Infrared Bullet Camera

- 1/3" Sony CMOS/ High Definition Serial Digital Interface
- HD-SDI (1080P, 720P)/ High Resolution (1000 TVLs)
- 0 Lux at IR on (IR LED: Varifocal 80pcs or MixH10/N55pcs)
- Upgraded Waterproof Housing (IP68 Rating)
- OSD Controlled/DNR (Digital Noise Reduction)
- True Day & Night(IRC)
- Motion Detection/ Privacy/ Easy Installation/ 4Axis
- DC Auto IRIS & TDN V/F Lens 2.8~12mm



Specifications

Resolution:	HD-SDI(1080P, 720P) / 1000 TV LINE OVER
Sensor:	1/3 INCH SONY CMOS
Total Pixels:	2010(H) X 1108(V) = 2,227,080
Effective Pixels:	1944(H) X 1092(V) = 2,122,648
Scanning System:	PROGRESSIVE
S/N (Y signal):	More than 52 dB (AGC Off)
Video Output:	SMPTE292M (HD-SDI) / CVBS: 1.0Vp-p (75ohm)
Min.Illumination:	0 Lux at IR On
White Balance:	AUTO / AUTO EXT / PUSHING / MANUAL
Electronic Shutter Speed:	Auto / Manual (1/30sec ~ 1/30,000sec)
Brightness:	ADJUSTABLE (0 ~ 20 STEP)
SENS_UP:	OFF / X2 / X3 / X4
DNR:	OFF / LOW / MIDDLE / HI
WDR/BLC:	OFF / WDR / BLC
HLM:	OFF / SET
ACE:	OFF / ON
Day & Night:	Auto (Day <--> Night TIME Change) , COLOR , B/W
Privacy:	OFF / ON (28 Zone)
Motion Detection:	OFF / ON
D.ZOOM:	0 ~ X112
FLIP:	OFF / ON
FREEZE:	OFF / ON
Language:	ENGLISH
Sharpness:	ADJUSTABLE (0 ~ 10 STEP)
Mirror:	ON / Off
COMM.:	RS-485(PELCO-D)
Operating Temp./Humidity:	-10'C~+50'C / 30%~80% RH
Storage Temp.Humidity:	-20'C~+60'C / 20%~90% RH
Power:	DC12V Only / DC12V·AC24V DualPower (option)
HS-SDI:	100 ~ 150m
Transmission Range:	Max transmission range is depends on the cable manufacturer and the installation