



HSR-4000

4 Channel Digital Video Recorder

- Hardware H.264 Compression
- Two Internal HDD Support - SATA3 up to 6 TB (2x3TB)
- Watermark Verification
- Password protected backup via USB, CD/DVD-RW, External USB HDD (Self Executable, No Codecs Required)
- Ramp Up Recording (Auto Change Video Quality & FPS triggered by event)
- PTZ Presets Triggered by Camera, Sensor, and/or Event
- Automatic Daylight Savings Update
- Multi-Platform Support
- Mac OSX(Native), Windows, Windows Mobile, Iphone, Android, Blackberry, and Nokia Symbian



Specifications

Operating System:	Embedded LINUX
Compression:	H.264
Audio Compression:	G723.1
Video Standard:	NTSC/PAL
Video:	Input: 4 Channel Output: Composite (1), Spot (1), S-VHS (1), VGA (1), Loop-Out (4) Resolution: Max. 1280 x 1024 Display Mode: TV, CCTV, VGA Monitor (Selectable)
Live:	Real Time View
Split Mode in Live Display:	1, 4
Record Resolution:	NTSC: CIF (352x240), 2CIF (704x240), D1 (704x480) PAL: CIF (352x288), 2CIF (704x288), D1 (704x576)
Record Speed:	CIF (NTSC/PAL): 120/100 fps 2CIF (NTSC/PAL): 120/100 fps D1 (NTSC/PAL): 120/100 fps
Record Mode:	Emergency, Schedule, Sensor, Motion, Sensor + Motion, Pre & Post Alarm Recording

